

CFS-MH



ADVANTAGES

- Extended surface multi-pocket filter
- Comprehensive range of standard sizes
- High efficiency
- Large surface area
- Controlled media spacing (CMS)

Applications: Air conditioning

Type: Extended surface multi pocket bag filter

Case: Galvanised steel

Media: Synthetic Fibres

EN 779:2002 filter class: F6, F7, F8

ASHRAE 52.2:1999 filter class: MERV 11, MERV 13, MERV 14

Recommended final pressure drop: 450 Pa (suggested economical change point 250 Pa)

Temperature: 70°C maximum in continuous service

Holding frames: Front and side access housings and frames are available, Type 8 and FC Housings.

Fire Rating: UL 900 Class 2



Model	Dimensions (WxHxD) mm	Filter classification EN 779:2002	Number of pockets	Media area m ²	Air Flow /pressure drop m ³ /hr/Pa	Unit weight (kg)	Unit volume m ³
CFS-MH6-10-66	592 x 592 x 534	F6	10	6.5	3400/65	2.7	0.05
CFS-MH6-8-65	490 x 592 x 534	F6	8	5.2	2800/65	2.4	0.05
CFS-MH6-5-63	287 x 592 x 534	F6	5	3.2	1700/65	1.6	0.03
CFS-MH7-10-66	592 x 592 x 534	F7	10	6.5	3400/75	2.7	0.05
CFS-MH7-8-65	490 x 592 x 534	F7	8	5.2	2800/75	2.4	0.05
CFS-MH7-5-63	287 x 592 x 534	F7	5	3.2	1700/75	1.6	0.03
CFS-MH8-10-66	592 x 592 x 534	F8	10	6.5	3400/95	2.7	0.05
CFS-MH8-8-65	490 x 592 x 534	F8	8	5.2	2800/95	2.4	0.05
CFS-MH8-5-63	287 x 592 x 534	F8	5	3.2	1700/95	1.6	0.03

* 20mm header frame is available on request